

Technical Datasheet - Tamper Evident Labels

Poly - Satin White Ultra Destructible

Label material:

A top-coated white destructible film.

Thickness: 50 micron $\pm 5\%$

Basic weight: 54 gsm $\pm 5\%$

Adhesive:

A permanent, rubber based adhesive.

Initial Tack: High

Final Adhesion: Very high

Minimum Application Temperature: $+15^{\circ}\text{C}$

Temperature Range: -40°C to $+100^{\circ}\text{C}$

UV Resistance: Good

Indoor use only.

Release liner:

A supercalendered siliconised white glassine paper.

Thickness: 56 micron $\pm 5\%$

Basic Weight: 60 gsm $\pm 15\%$

Poly - Matt Silver Void

Label material:

A matt silver, top-coated polyester security film with void text. Designed for security applications such as sealing labels on products.

Thickness: 52 micron $\pm 5\%$

Basic weight: 71 gsm $\pm 5\%$

Adhesive:

A strong permanent, UV acrylic adhesive. Very good temperature and chemical resistance properties.

Initial Tack: Good

Final Adhesion: High

Minimum Application Temperature: $+5^{\circ}\text{C}$

Temperature Range: -40°C to $+200^{\circ}\text{C}$

UV Resistance: Good

This adhesive is designed for universal labelling applications on polar and non-polar surfaces with very good temperature and chemical resistance properties.

Release liner:

A supercalendered transparent white glassine paper.

Thickness: 54 micron $\pm 5\%$

Basic Weight: 62 gsm $\pm 5\%$